


DECKMA HAMBURG GmbH

15ppm Bilge Alarm OMD-2008

According to regulations of IMO Resolution MEPC. 107(49)
U.S. Coast Guard approved



We help to protect the Environment



DECKMA HAMBURG GmbH

DECKMA Decksmaschinen und Automation Vertriebsgesellschaft in Hamburg mbH

SPECIFICATION OMD-2008

Range:	0 – 30 ppm, Trend up to 50 ppm
Accuracy:	According IMO MEPC. 107(49)
Linearity:	Up to 30 ppm better than $\pm 2 \%$
Display:	Graphic Display
Power Supply:	24 V – 240 V AC or DC Automatic Voltage Selection
Consumption:	< 10 VA
Alarm Points 1 + 2:	Adjustable between 1 - 15 ppm (Works adjustment 15 ppm)
Alarm 1 Operating Delay: (for annunciation purpose)	Adjustable between 1 – 540 sec. (Works adjustment 2 sec.)
Alarm 2 Operating Delay: (for control purposes)	Adjustable between 1 – 10 sec. (Works adjustment 10 sec.)
System Fault Alarm:	Red LED
Alarm Contact Rating:	Potential free 1-pole change over contacts, 3 A / 240 V
Alarm Indication:	Red LED's
Output Signal:	0 – 20 mA or 4 – 20 mA, reversible ext. Load < 150 Ohm
Sample Water Pressure:	0,1 – 10 bar
Sample Flow:	Approx. 0,1 - 3 l/min. depending to pressure
Ambient Temperature:	+ 1 to + 55° C
Sample Water Temperature:	+ 1 to + 65° C
Roll:	Up to 45°
Size (over all):	360 mm W x 240 mm H x 100 mm D
Degree of Protection:	IP 65
Weight:	5,4 kgs
Pipe Connections:	R 1/4" Female

Contacts / Enquiries:

Agent:

DECKMA HAMBURG GmbH

Phone: +49 (0) 40 54 88 76 -0
Fax: +49 (0) 40 54 88 76 -10
eMail: post@deckma.com
Internet: www.deckma.com

Postal Address: Kieler Strasse 316
22525 Hamburg
Germany

Contika Aps
Hindhøjten 82
8382 Hinnerup
Tel 86245066
www.contika.dk